

MK 2/12**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Multi-pole terminal strips are suitable for wiring in junction boxes and small distribution boxes. The different numbers of poles offer the possibilities of direct mounting inside the housings.

General ordering data

| | |
|------------|---|
| Version | Single- and multi-pole terminal strip, Screw connection, 2.5 mm ² , 125 V, 24 A, Number of poles: 12, 15 mm, beige |
| Order No. | 0241260000 |
| Type | MK 2/12 |
| GTIN (EAN) | 4008190026738 |
| Qty. | 50 pc(s). |

MK 2/12**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

| | | | |
|------------|--------|-----------------|------------|
| Depth | 15 mm | Depth (inches) | 0.591 inch |
| Height | 86 mm | Height (inches) | 3.386 inch |
| Width | 15 mm | Width (inches) | 0.591 inch |
| Net weight | 33.6 g | | |

Temperatures

| | | | |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 100 °C | | |

Material data

| | | | |
|---------------------------|--------------|--------|-------|
| Material | Polyamide 66 | Colour | beige |
| UL 94 flammability rating | V-2 | | |

System specifications

| | | | |
|---------|------------------------|--------------------------|----|
| Version | For the mounting rails | End cover plate required | No |
|---------|------------------------|--------------------------|----|

Additional technical data

| | | | |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of mounting | Direct mounting | | |

CSA rating data

| | | | |
|-------------------------------|-------------------|-------------------------------|--------|
| Certificate No. (CSA) | 12400-161-162-163 | Current size B (CSA) | 10 A |
| Current size D (CSA) | 10 A | Voltage size B (CSA) | 300 V |
| Voltage size D (CSA) | 300 V | Wire cross section max. (CSA) | 12 AWG |
| Wire cross section min. (CSA) | 24 AWG | | |

Conductors for clamping (additional connection)

| | |
|--|------------------|
| Connection type, additional connection | Screw connection |
|--|------------------|

MK 2/12

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Conductors for clamping (rated connection)

| | | | |
|---|---------------------|---|---------------------|
| Blade size | 0.6 x 3.5 mm | Clamping range, max. | 4 mm ² |
| Clamping range, min. | 0.2 mm ² | Clamping screw | M 2.5 |
| Connection cross-section, stranded, max. | 2.5 mm ² | Connection cross-section, stranded, min. | 1.5 mm ² |
| Connection direction | on side | Gauge to IEC 60947-1 | A2 |
| Number of connections | 24 | Stripping length | 5 mm |
| Tightening torque, max. | 0.4 Nm | Torque level with DMS electric screwdriver | 1 |
| Type of connection | Screw connection | Wire connection cross section AWG, max. | AWG 12 |
| Wire connection cross section AWG, min. | AWG 24 | Wire connection cross section, finely stranded, max. | 2.5 mm ² |
| Wire connection cross section, finely stranded, min. | 0.5 mm ² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 1.5 mm ² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 mm ² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 1.5 mm ² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 mm ² | Wire connection cross-section, solid core, max. | 4 mm ² |
| Wire connection cross-section, solid core, min. | 0.5 mm ² | | |

General

| | | | |
|---|-----------------|---|--------|
| Installation advice | Direct mounting | Number of poles | 12 |
| Standards | IEC 60947-7-1 | Wire connection cross section AWG, max. | AWG 12 |
| Wire connection cross section AWG, min. | AWG 24 | | |

Rating data

| | | | |
|--|---------------------|---------------------------------|---------------|
| Rated cross-section | 2.5 mm ² | Rated voltage | 125 V |
| Rated DC voltage | 125 V | Rated current | 24 A |
| Current at maximum wires | 24 A | Standards | IEC 60947-7-1 |
| Volume resistance according to IEC 60947-7-x | 1.33 mΩ | Rated impulse withstand voltage | 2.5 kV |
| Power loss in accordance with IEC 60947-7-x | 0.77 W | Pollution severity | 3 |

UL rating data

| | | | |
|---|--------|---|--------|
| Certificate No. (UR) | E60693 | Conductor size Factory wiring max. (UR) | 12 AWG |
| Conductor size Factory wiring min. (UR) | 24 AWG | Conductor size Field wiring max. (UR) | 12 AWG |
| Conductor size Field wiring min. (UR) | 24 AWG | Current size B (UR) | 10 A |
| Current size D (UR) | 10 A | Voltage size B (UR) | 300 V |
| Voltage size D (UR) | 300 V | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001284 | ETIM 7.0 | EC001284 |
| ETIM 8.0 | EC001284 | ETIM 9.0 | EC001284 |
| ECLASS 9.0 | 27-14-11-06 | ECLASS 9.1 | 27-14-11-06 |
| ECLASS 10.0 | 27-14-11-06 | ECLASS 11.0 | 27-14-11-06 |
| ECLASS 12.0 | 27-14-11-06 | ECLASS 13.0 | 27-14-11-06 |

Creation date July 7, 2024 9:01:54 PM CEST

MK 2/12

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Environmental Product Compliance

REACH SVHC

/

Approvals

Approvals



ROHS Conform

UL File Number Search UL Website

Certificate No. (UR) E60693

Downloads

| | |
|---|---|
| Approval/Certificate/Document of Conformity | Declaration of Conformity UKCA declaration of conformity |
| Engineering Data | CAD data – STEP |
| User Documentation | StorageConditionsTerminalBlocks |
| Catalogues | Catalogues in PDF-format |
| Brochures | |