

**QL 10 SAKS2****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Similar to illustration

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

|                 |   |
|-----------------|---|
| Version         | Cross-connector (terminal), when screwed in, Number of poles: 10, Pitch in mm (P): 10.00, Insulated: No, 36 A, grey |
| Order No.       | <a href="#">0338900000</a>  |
| Type            | QL 10 SAKS2   |
| GTIN (EAN)      | 4008190105723   |
| Qty.            | 20 pc(s).   |
| Delivery status | <b>This article will no longer be available in the future.</b>  |
| Available until | 2024-12-31  |

Creation date July 7, 2024 8:03:25 PM CEST

Catalogue status 29.06.2024 / We reserve the right to make technical changes.

**QL 10 SAKS2**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |          |                 |             |
|------------|----------|-----------------|-------------|
| Depth      | 4 mm     | Depth (inches)  | 0.157 inch  |
| Height     | 10 mm    | Height (inches) | 0.394 inch  |
| Width      | 261.4 mm | Width (inches)  | 10.291 inch |
| Net weight | 82.6 g   |                 |             |

**Temperatures**

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

**Material data**

|          |        |        |      |
|----------|--------|--------|------|
| Material | Copper | Colour | grey |
|----------|--------|--------|------|

**System specifications**

|         |                           |
|---------|---------------------------|
| Version | for cross-connection link |
|---------|---------------------------|

**Additional technical data**

|                          |                 |                     |                 |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No              | Installation advice | Direct mounting |
| Type of fixing           | when screwed in |                     |                 |

**Cross-connector**

|                                     |      |                       |                 |
|-------------------------------------|------|-----------------------|-----------------|
| Number of cross-connected terminals | 10   | Rated current, 2-pole | 36 A            |
| Rated current, multi-pole           | 36 A | Type                  | Cross-connector |

**Dimensions**

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 10 mm |
|-----------------|-------|

**General**

|                     |                 |                 |    |
|---------------------|-----------------|-----------------|----|
| Installation advice | Direct mounting | Number of poles | 10 |
|---------------------|-----------------|-----------------|----|

**Rating data**

|               |      |
|---------------|------|
| Rated current | 36 A |
|---------------|------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ETIM 9.0    | EC000489    |
| ECLASS 9.0  | 27-14-11-40 | ECLASS 9.1  | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |
| ECLASS 12.0 | 27-14-11-40 | ECLASS 13.0 | 27-25-03-03 |

**Environmental Product Compliance**

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

Creation date July 7, 2024 8:03:25 PM CEST

**QL 10 SAKS2**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Technical data****Downloads**

|                    |   |
|--------------------|---|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| Engineering Data   | <a href="#">Zuken E3.S</a>                      |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>        |
| Brochures          |   |

**QL 10 SAKS2**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Accessories**

**Screws**



Depending on the terminal block or also accessories, we offer different types of screws as additional items or also spare parts.

**General ordering data**

|            |                            |                           |
|------------|----------------------------|---------------------------|
| Type       | BFSC M4X9T                 | Version                   |
| Order No.  | <a href="#">0103300000</a> | Mounting screw (Terminal) |
| GTIN (EAN) | 4008190023348              |                           |
| Qty.       | 100 pc(s).                 |                           |

**Miscellaneous**



We offer a broad portfolio of mounting support for easy handling and supplementation of our products. From various tools to insulating sleeves and various screws, our components are matched to each other down to the last detail and thus facilitate assembly in compliance with the respective standards and protective regulations.

**General ordering data**

|            |                            |                     |
|------------|----------------------------|---------------------|
| Type       | SS M4 D 128-A 4            | Version             |
| Order No.  | <a href="#">0136400000</a> | Lock washer, Copper |
| GTIN (EAN) | 4008190118143              |                     |
| Qty.       | 100 pc(s).                 |                     |