

**SSCH 15X6X1000 CU/SN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Of all the metals used, copper has the best electrical conductivity, which results in the highest short-circuit resistance. This makes the copper busbar the most widely used variant.

**General ordering data**

Version	Busbar (terminal)
Order No.	<a href="#">0357400000</a>
Type	SSCH 15X6X1000 CU/SN
GTIN (EAN)	4008190169572
Qty.	1 m

**SSCH 15X6X1000 CU/SN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

Depth	6 mm	Depth (inches)	0.236 inch
Height	1,000 mm	Height (inches)	39.37 inch
Width	15 mm	Width (inches)	0.591 inch
Net weight	796.35 g		

**Material data**

Material	Copper	Surface finish	tinned
Colour	silver		

**System specifications**

Version	15 x 6 mm busbar connection
---------	-----------------------------

**Additional technical data**

Installation advice	Direct mounting
---------------------	-----------------

**General**

Installation advice	Direct mounting	Surface finish	tinned
---------------------	-----------------	----------------	--------

**Rating data**

Rated current	265 A
---------------	-------

**Classifications**

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ETIM 8.0	EC002848	ETIM 9.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-92
ECLASS 12.0	27-14-11-92	ECLASS 13.0	27-14-11-92

**Environmental Product Compliance**

REACH SVHC	/
------------	---

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">CAD data – STEP</a>
User Documentation	<a href="#">Storage Conditions</a> <a href="#">Terminal Blocks</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	