

**WAP 2.5-10 GR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

**General ordering data**

|            |   |
|------------|---|
| Version    | End plate (terminals), 56 mm x 1.5 mm, grey |
| Order No.  | <a href="#">1050050000</a>                  |
| Type       | WAP 2.5-10 GR                               |
| GTIN (EAN) | 4008190455484                               |
| Qty.       | 50 pc(s).                                   |

**WAP 2.5-10 GR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 33.5 mm | Depth (inches)  | 1.319 inch |
| Height     | 56 mm   | Height (inches) | 2.205 inch |
| Width      | 1.5 mm  | Width (inches)  | 0.059 inch |
| Net weight | 2.581 g |                 |            |

**Temperatures**

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

**Material data**

|                           |       |        |      |
|---------------------------|-------|--------|------|
| Material                  | Wemid | Colour | grey |
| UL 94 flammability rating | V-0   |        |      |

**System specifications**

|         |           |
|---------|-----------|
| Version | End plate |
|---------|-----------|

**Additional technical data**

|                     |                 |         |    |
|---------------------|-----------------|---------|----|
| Installation advice | Direct mounting | Snap-on | No |
|---------------------|-----------------|---------|----|

**Dimensions**

|              |       |
|--------------|-------|
| TS 35 offset | 66 mm |
|--------------|-------|

**General**

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000886    | ETIM 7.0    | EC000886    |
| ETIM 8.0    | EC000886    | ETIM 9.0    | EC000886    |
| ECLASS 9.1  | 27-14-11-33 | ECLASS 10.0 | 27-14-11-33 |
| ECLASS 11.0 | 27-14-11-33 | ECLASS 12.0 | 27-14-11-33 |
| ECLASS 13.0 | 27-25-03-01 |             |             |

**Environmental Product Compliance**

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## WAP 2.5-10 GR

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|  |  |
|--|--|
| Approval/Certificate/Document of Con-<br>formity | <a href="#">Confirmation of Standards EN 45545-2_2020-10</a> |
| Engineering Data                                 | <a href="#">CAD data – STEP</a>                              |
| Engineering Data                                 | <a href="#">Zuken E3.S</a>                                   |
| User Documentation                               | <a href="#">StorageConditionsTerminalBlocks</a>              |
| Catalogues                                       | <a href="#">Catalogues in PDF-format</a>                     |