

**FZS 2/4 RT/80 SAKT4****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

**General ordering data**

|            |   |
|------------|---|
| Version    | Plug (terminal), Plug-in connection, red, 2 mm <sup>2</sup> , Number of connections: 2, Number of poles: 1, Width: 9 mm, Height: 9 mm |
| Order No.  | <a href="#">1276300000</a>  |
| Type       | FZS 2/4 RT/80 SAKT4   |
| GTIN (EAN) | 4008190026080   |
| Qty.       | 20 pc(s).   |

**FZS 2/4 RT/80 SAKT4****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|          |        |                 |            |
|----------|--------|-----------------|------------|
| Depth    | 100 mm | Depth (inches)  | 3.937 inch |
| Height   | 9 mm   | Height (inches) | 0.354 inch |
| Width    | 9 mm   | Width (inches)  | 0.354 inch |
| Diameter | 9 mm   | Net weight      | 4.92 g     |

**Material data**

|        |     |
|--------|-----|
| Colour | red |
|--------|-----|

**System specifications**

|         |              |
|---------|--------------|
| Version | Adapter plug |
|---------|--------------|

**Additional technical data**

|                     |                 |                |         |
|---------------------|-----------------|----------------|---------|
| Installation advice | Direct mounting | Type of fixing | Plugged |
| Type of mounting    | Plugged         |                |         |

**Conductors for clamping (rated connection)**

|                       |   |                    |                    |
|-----------------------|---|--------------------|--------------------|
| Number of connections | 2 | Type of connection | Plug-in connection |
|-----------------------|---|--------------------|--------------------|

**Dimensions**

|          |      |
|----------|------|
| Diameter | 9 mm |
|----------|------|

**General**

|                     |                 |                 |   |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 1 |
|---------------------|-----------------|-----------------|---|

**Rating data**

|                     |                   |
|---------------------|-------------------|
| Rated cross-section | 2 mm <sup>2</sup> |
|---------------------|-------------------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002848    | ETIM 7.0    | EC002848    |
| ETIM 8.0    | EC002848    | ETIM 9.0    | EC002848    |
| ECLASS 9.0  | 27-14-11-92 | ECLASS 9.1  | 27-14-11-92 |
| ECLASS 10.0 | 27-14-11-92 | ECLASS 11.0 | 27-14-11-92 |
| ECLASS 12.0 | 27-14-11-92 | ECLASS 13.0 | 27-25-03-90 |
| ECLASS 14.0 | 27-25-03-90 |             |             |

**Environmental Product Compliance**

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| REACH SVHC                           | Lead 7439-92-1                       |
| SCIP                                 | 5837f5db-79d4-4531-bf95-fd2b6e115085 |
| RoHS Compliance Status               | Compliant with exemption             |
| RoHS Exemption (if applicable/known) | 6aI, 6c                              |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### FZS 2/4 RT/80 SAKT4

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

User Documentation

[StorageConditionsTerminalBlocks](#)

Catalogues

[Catalogues in PDF-format](#)