

**VPU II 2 PV 600V DC****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**General ordering data**

Version	Surge voltage arrester, Low voltage, without telecomm. contact
Order No.	<a href="#">1351340000</a>
Type	VPU II 2 PV 600V DC
GTIN (EAN)	4050118158731
Qty.	1 pc(s).
Replacement parts	<a href="#">1351320000</a>

## VPU II 2 PV 600V DC

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Depth	69 mm	Depth (inches)	2.717 inch
Height	94 mm	Height (inches)	3.701 inch
Width	35.6 mm	Width (inches)	1.402 inch
Mounting dimension - height	75 mm	Net weight	290 g

## Temperatures

Storage temperature	-40 °C...80 °C	Operating temperature	-40 °C...70
---------------------	----------------	-----------------------	-------------

## General data

Colour	black, orange	Design	Installation housing; 2TE, Insta IP 20
Operating altitude	≤ 2000 m	Optical function display	green = OK; red = arrester is defective - replace
Protection degree	IP20	Rail	TS 35
UL 94 flammability rating	V-0	Version	without telecomm. contact

## Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

## Photovoltaic technical data

Discharge current $I_n$ (8/20 $\mu$ s)	12.5 kA	Discharge current, max. (8/20 $\mu$ s)	40 kA
Maximum continuous operating voltage DC UCPV mode +/-, -/PE, +/-PE	600 V	Operating height in the grounded PV system	≤ 2000 m
Operating height in ungrounded PV system	≤ 2000 m	PV system voltage, max. $U_{cpv}$	600 V
Protection level $U_p$ (+/-)	≤ 4.4 kV	Protection level $U_p$ (+/PE)	≤ 2.2 kV
Protection level $U_p$ (-/PE)	≤ 2.2 kV	Requirements class	Type II
Short-circuit current $I_{SCPv}$	200 A	Standards	EN 50539-11
Total discharge current $I_{total}$ (8/20 $\mu$ s)	40		

## Rated data IEC / EN

Discharge current $I_n$ (8/20 $\mu$ s) wire-PE	20 kA	Discharge current, max. (8/20 $\mu$ s)	40 kA
Leakage current at $U_n$	30 $\mu$ A	Max. continuous voltage, $U_c$ (DC)	600 V
Number of poles	2	PV voltage, acc. to IEC 60364-7-712	< 600 V
Rated voltage (DC)	600 V	Response time	≤ 25 ns
SPD type	T2	Signalling contact	No
Standards	EN 50539-11	Voltage type	DC

## VPU II 2 PV 600V DC

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Connection data

Stripping length	15 mm	Type of connection	Screw connection
Stripping length, rated connection	15 mm	Tightening torque, min.	2 Nm
Tightening torque, max.	3 Nm	Clamping range, rated connection	16 mm <sup>2</sup>
Clamping range, min.	1.5 mm <sup>2</sup>	Clamping range, max.	35 mm <sup>2</sup>
Wire cross-section, solid, min.	1.5 mm <sup>2</sup>	Wire cross-section, solid, max.	16 mm <sup>2</sup>
Wire connection cross section, finely stranded, min.	1.5 mm <sup>2</sup>	Wire connection cross section, finely stranded, max.	25 mm <sup>2</sup>
Conductor cross-section, flexible, AEH (DIN 46228-1), min.	1.5 mm <sup>2</sup>	Conductor cross-section, flexible, AEH (DIN 46228-1), max.	50 mm <sup>2</sup>
Connection cross-section, stranded, min.	1.5 mm <sup>2</sup>	Connection cross-section, stranded, max.	50 mm <sup>2</sup>

## Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
ETIM 8.0	EC000941	ETIM 9.0	EC000941
ECLASS 9.0	27-13-08-05	ECLASS 9.1	27-13-08-05
ECLASS 10.0	27-13-08-05	ECLASS 11.0	27-13-08-05
ECLASS 12.0	27-17-90-90	ECLASS 13.0	27-17-90-90

## Tender specification sheets

Long specification	<p>Multi-pole surge voltage arrester according to the requirements of Class II acc. to IEC 50539-11. Consisting of V0 material, the arrester serves as overvoltage protection and is used in applications according to IEC 50539-12. The use of a high-performance varistor meets the inspection requirements for Class II surge protection systems on the basis of the standards. The arrester is installed in the vicinity of the equipment that needs protection, in a commercially available installation/electrical distribution enclosure. With thermal separation device on the varistor. If protection is no longer available, the colour in the display window changes from green to red. Rated voltage: 600 VAC In/max (8/20 µs): 20/40 kA, protection level &lt; 2.2 kV I, type: Weidmüller VPU II 2 PV 600 V/40 kA, Order No. 135 13400000 or equivalent</p>	<p>Short specification</p> <p>Class II arrester with In/Imax: 20/40 kA suitable for 600 V PV systems. Protection level &lt; 2.2 kV. Type: Weidmüller VPU II 2 PV 600 V/40 kA Order no. 135 13400000 or equivalent</p>
--------------------	--	---

## Environmental Product Compliance

REACH SVHC

/

## VPU II 2 PV 600V DC

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Approvals

Approvals



ROHS

Conform

### Downloads

Approval/Certificate/Document of Conformity

[EU\\_Konformitätserklärung / EU\\_Declaration\\_of\\_Conformity](#)

Engineering Data

[CAD data – STEP](#)

User Documentation

[Beipackzettel / Instruction sheet](#)

Catalogues

[Catalogues in PDF-format](#)

Brochures


## VPU II 2 PV 600V DC

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Electric symbol



Circuit diagram

**VPU II 2 PV 600V DC****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Crosshead screwdriver Phillips**

VDE insulated crosshead screwdriver, for Phillips screws, SDIK PH DIN 7438, ISO 8764/2-PH, output to ISO 8764-PH, SoftFinish grip

**General ordering data**

Type	SDIK PH1 X 80	Version
Order No.	<a href="#">2749890000</a>	Screwdriver, Blade width (B): 1 mm, 80 mm, Blade thickness (A): 1
GTIN (EAN)	4050118897098	
Qty.	1 pc(s).	

**VPU II 2 PV 600V DC****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Replacement parts****Spare Arrester****General ordering data**

Type	VPU II 0 PV 600V DC	Version
Order No.	<a href="#">1351320000</a>	Surge voltage arrester, Low voltage, Accessories, Surge protection II
GTIN (EAN)	4050118158755	
Qty.	1 pc(s).	