

**HDC HQP ALU CS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**IP65**

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection. The HQ version now offers particular protection - the bulkhead housing (cover and metal clamp) can be secured with a padlock.

**General ordering data**

|            |  |
|------------|--|
| Version    | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Bulkhead housing, Side-locking clamp on lower side, Standard |
| Order No.  | <a href="#">1354950000</a>   |
| Type       | HDC HQP ALU CS   |
| GTIN (EAN) | 4050118157215  |
| Qty.       | 1 pc(s).   |

## HDC HQP ALU CS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                             |       |                            |            |
|-----------------------------|-------|----------------------------|------------|
| Depth                       | 67 mm | Depth (inches)             | 2.638 inch |
| Height                      | 41 mm | Height (inches)            | 1.614 inch |
| Width                       | 35 mm | Width (inches)             | 1.378 inch |
| Mounting dimension - height | 13 mm | Mounting dimension - width | 32 mm      |
| Net weight                  | 27 g  |                            |            |

## Temperatures

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 125 °C |
|-------------------|-------------------|

## Dimensions

|                      |       |                      |       |
|----------------------|-------|----------------------|-------|
| Height of housing B  | 20 mm | Hole pitch length A2 | 32 mm |
| Total length housing | 46 mm | Width housing C      | 29 mm |

## General data

|                             |                             |                           |                             |
|-----------------------------|-----------------------------|---------------------------|-----------------------------|
| EMC housings                | No                          | Housing main material     | Plastic                     |
| Material of locking element | Stainless steel, rust-proof | Protection degree         | IP65 (in plugged condition) |
| Series                      | HQ                          | UL 94 flammability rating | V-0                         |

## Version

|                        |                         |                          |                                  |
|------------------------|-------------------------|--------------------------|----------------------------------|
| BG                     | HQ                      | Clamp version            | Side-locking clamp               |
| Colour (RAL)           | RAL 1001                | Design                   | Standard                         |
| Design of housing      | Bulkhead housing        | Design of locking system | Side-locking clamp on lower side |
| Sealing                | NBR                     | Size                     | HQ                               |
| Suitable for ModuPlug® | No                      | Top part/bottom part/lid | lower part                       |
| Type                   | Bulkhead (feed-through) |                          |                                  |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000437    | ETIM 7.0    | EC000437    |
| ETIM 8.0    | EC000437    | ETIM 9.0    | EC000437    |
| ECLASS 9.0  | 27-44-02-02 | ECLASS 9.1  | 27-44-02-02 |
| ECLASS 10.0 | 27-44-02-02 | ECLASS 11.0 | 27-44-02-02 |
| ECLASS 12.0 | 27-44-02-02 | ECLASS 13.0 | 27-44-02-02 |

|                     |                         |
|---------------------|-------------------------|
| Substance           | Acetone                 |
| Chemical resistance | Conditionally resistant |
| Substance           | Drilling oil            |
| Chemical resistance | Resistant               |
| Substance           | Diesel                  |
| Chemical resistance | Resistant               |
| Substance           | Ethyl alcohol           |
| Chemical resistance | Resistant               |
| Substance           | Transmission oil        |
| Chemical resistance | Resistant               |

## HDC HQP ALU CS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|                     |                         |
|---------------------|-------------------------|
| Substance           | Hydraulic oil           |
| Chemical resistance | Resistant               |
| Substance           | Coolant                 |
| Chemical resistance | Resistant               |
| Substance           | Petroleum benzine       |
| Chemical resistance | Resistant               |
| Substance           | Sweat                   |
| Chemical resistance | Resistant               |
| Substance           | Premium gasoline        |
| Chemical resistance | Conditionally resistant |
| Substance           | Water                   |
| Chemical resistance | Resistant               |
| Substance           | UV                      |
| Chemical resistance | Unstable                |
| Substance           | Ozone                   |
| Chemical resistance | Unstable                |

## Environmental Product Compliance

|                     |   |
|---------------------|---|
| REACH SVHC          | Potassium perfluorobutane sulfonate 29420-49-3  |
| SCIP                | 2f94735a-9fba-4903-842f-4fb9aa902310  |
| Chemical resistance | de.myview.objectmodel.impl.BlockImpl@5dee7978 de.myview.objectmodel.impl.BlockImpl@33623171<br>de.myview.objectmodel.impl.BlockImpl@4fef2a6d de.myview.objectmodel.impl.BlockImpl@15674ac7<br>de.myview.objectmodel.impl.BlockImpl@3becc4aa de.myview.objectmodel.impl.BlockImpl@19a7931f<br>de.myview.objectmodel.impl.BlockImpl@2f2d7e04 de.myview.objectmodel.impl.BlockImpl@b32854<br>de.myview.objectmodel.impl.BlockImpl@5d27757c de.myview.objectmodel.impl.BlockImpl@78bd2aac<br>de.myview.objectmodel.impl.BlockImpl@3ca4b6e1 de.myview.objectmodel.impl.BlockImpl@25ccc8a9<br>de.myview.objectmodel.impl.BlockImpl@4326c5f9 |

## Important note

|                     |   |
|---------------------|---|
| Product information | The HQ version now offers particular protection - the bulkhead housing (cover and metal clamp) can be secured with a padlock. |
|---------------------|---|

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|   |  |
|---|--|
| Approval/Certificate/Document of Conformity | <a href="#">Manufacturer's declaration</a>   |
| Product Change Notification                 | <a href="#">20220214 Technical change to HDC housings</a><br><a href="#">20220214 Technische Änderung bei HDC-Gehäusen</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>   |
| Brochures                                   | <a href="#">FL FIELDWIRING EN</a><br><a href="#">FL FIELDWIRING EN</a>   |

Creation date July 7, 2024 9:48:01 PM CEST


Catalogue status 29.06.2024 / We reserve the right to make technical changes.

## HDC HQP ALU CS

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



## HDC HQP ALU CS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Plug housing, cable entry sideways



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection. The HQ version now offers particular protection - the bulkhead housing (cover and metal clamp) can be secured with a padlock.

## General ordering data

| Type       | HDC HQM TSLU 1PG21         | Version  |
|------------|----------------------------|--|
| Order No.  | <a href="#">1003100000</a> | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, Side-locking clamp on |
| GTIN (EAN) | 4032248698035              | lower side, Standard, Size of cable entries: PG 21   |
| Qty.       | 1 pc(s).                   |  |

## Cover



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection. The HQ version now offers particular protection - the bulkhead housing (cover and metal clamp) can be secured with a padlock.

## General ordering data

| Type       | HDC HQP DOD 2B0            | Version  |
|------------|----------------------------|--|
| Order No.  | <a href="#">1003140000</a> | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Cover for lower part of housing, Side-locking clamp on |
| GTIN (EAN) | 4032248698073              | lower side, Standard   |
| Qty.       | 1 pc(s).                   |  |

## HDC HQP ALU CS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

|            |                            |   |
|------------|----------------------------|---|
| Type       | HDC HQP DOD 2BO CS         | Version   |
| Order No.  | <a href="#">1251670000</a> | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Cover for lower part of housing, Side-locking clamp on lower side           |
| GTIN (EAN) | 4050118052329              |   |
| Qty.       | 1 pc(s).                   |   |
| Type       | HDC HQP DMD 2BO CS         | Version   |
| Order No.  | <a href="#">1251660000</a> | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Cover for lower part of housing, Side-locking clamp on lower side           |
| GTIN (EAN) | 4050118052312              |   |
| Qty.       | 1 pc(s).                   |   |
| Type       | HDC HQP DMD 2BO            | Version   |
| Order No.  | <a href="#">1003130000</a> | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Cover for lower part of housing, Side-locking clamp on lower side, Standard |
| GTIN (EAN) | 4032248698066              |   |
| Qty.       | 1 pc(s).                   |   |

## Plug housing, cable entry at top



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection. The HQ version now offers particular protection - the bulkhead housing (cover and metal clamp) can be secured with a padlock.

## General ordering data

|            |                            |  |
|------------|----------------------------|--|
| Type       | HDC HQP TOLU 1PG16         | Version  |
| Order No.  | <a href="#">1003070000</a> | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, Side-locking clamp on lower side, Standard, Size of cable entries: PG 16 |
| GTIN (EAN) | 4032248698004              |  |
| Qty.       | 1 pc(s).                   |  |

## HDC HQP ALU CS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## 4/2-pole



The HQ series - big features in a compact design. The electrical characteristics speak for themselves. You can also use the proven HD and HX crimp contacts here. The wire connection level is designed for crimp contacts. The proven crimp connection has been in standard use for decades.

Crimp contacts are not included in the scope of delivery of inserts.

Pole count: **4/2 (+PE)**

Rated current: **40/10 A**

Rated voltage: **690 / 250 V**

Rated voltage acc. to UL/CSA: **600 V AC/DC**

Crimp connection

## General ordering data

| Type       | HDC HQ 4/2 MC              | Version  |
|------------|----------------------------|--|
| Order No.  | <a href="#">1003170000</a> | HDC insert, Male, 690 V, 40 A, Number of poles: 6, Crimp connection, |
| GTIN (EAN) | 4032248698165              | Size: HQ   |
| Qty.       | 1 pc(s).                   |  |
| Type       | HDC HQ 4/2 FC              | Version  |
| Order No.  | <a href="#">1003160000</a> | HDC insert, Female, 690 V, 40 A, Number of poles: 6, Crimp           |
| GTIN (EAN) | 4032248698158              | connection, Size: HQ   |
| Qty.       | 1 pc(s).                   |  |

## 17-pole



The HQ series - big features in a compact design The electrical values speak for themselves. The standard HE crimp contacts can also be used here.

The wire connection level is designed as a crimp contact The established crimp connection has been used as a standard for decades.

Crimp contacts are not delivered with the inserts.

Pole count: **17 (+PE)**

Rated current: **10 A**

Rated voltage **250 V**

Nominal voltage acc. to UL/CSA: **600 V AC/DC**

Crimp connection

## General ordering data

| Type       | HDC HQ 17 MC               | Version   |
|------------|----------------------------|---|
| Order No.  | <a href="#">1003210000</a> | HDC insert, Male, 250 V, 10 A, Number of poles: 17, Crimp   |
| GTIN (EAN) | 4032248698202              | connection, Size: HQ  |
| Qty.       | 1 pc(s).                   |   |
| Type       | HDC HQ 17 FC               | Version   |
| Order No.  | <a href="#">1003200000</a> | HDC insert, Female, 250 V, 10 A, Number of poles: 17, Crimp |
| GTIN (EAN) | 4032248698196              | connection, Size: HQ  |
| Qty.       | 1 pc(s).                   |   |

## HDC HQP ALU CS

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## 8-pole



A small size but quite big. The electrical values speak for themselves. Proven HE crimp contacts can also be used here.

Pole count: **8 (+PE)**Rated current: **16 A**Rated voltage: **500 V**Nominal voltage acc. to UL/CSA: **600 V AC/DC**

Crimp connection

## General ordering data

|            |                            |   |
|------------|----------------------------|---|
| Type       | HDC HQ 8 FC                | Version   |
| Order No.  | <a href="#">1919980000</a> | HDC insert, Female, 500 V, 16 A, Number of poles: 8, Crimp connection, Size: HQ |
| GTIN (EAN) | 4032248557950              |   |
| Qty.       | 1 pc(s).                   |   |
| Type       | HDC HQ 8 MC                | Version   |
| Order No.  | <a href="#">1919970000</a> | HDC insert, Male, 500 V, 16 A, Number of poles: 8, Crimp connection, Size: HQ   |
| GTIN (EAN) | 4032248557943              |   |
| Qty.       | 1 pc(s).                   |   |

## Plug housing, cable entry sideways



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection. The HQ version now offers particular protection - the bulkhead housing (cover and metal clamp) can be secured with a padlock.

## General ordering data

|            |                            |   |
|------------|----------------------------|---|
| Type       | HDC HQP TSLU 1PG16         | Version   |
| Order No.  | <a href="#">1003090000</a> | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, Side-locking clamp on lower side, Standard, Size of cable entries: PG 16 |
| GTIN (EAN) | 4032248698028              |   |
| Qty.       | 1 pc(s).                   |   |



**HDC HQP ALU CS****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Plug housing, cable entry at top**

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection. The HQ version now offers particular protection - the bulkhead housing (cover and metal clamp) can be secured with a padlock.

**General ordering data**

|            |                            |   |
|------------|----------------------------|---|
| Type       | HDC HQM TOLU 1PG21         | Version   |
| Order No.  | <a href="#">1003080000</a> | HDC enclosures, Size: HQ, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, Side-locking clamp on |
| GTIN (EAN) | 4032248698011              | lower side, Standard, Size of cable entries: PG 21  |
| Qty.       | 1 pc(s).                   |   |