

KLIPPON COPL 163609**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

The Klippon® POK enclosure range is made from a high-quality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class are a requirement.

Key features of the extensive product range:

- Available in 17 sizes
- Two standard finishes (colours): grey (similar to RAL 7001 for industrial use) and black (similar to RAL 9011 for harsh environments, Ex)
- Cover with stainless steel screws in cross-head / slotted design
- Moulded gasket made of silicone or chloroprene
- Fixing holes outside the sealed area to ensure high ingress protection of IP66
- Impact resistance up to 7 Joules
- Mounting directly in the enclosure or using an internal mounting plate
- Direct wall mounting possible using fixing holes or mounting feet
- Fastening thread to attach mounting rails and plates
- Up to E60 fire rating dependent on the configuration
- Weidmüller can manufacture and supply this enclosure to match customer specifications - fitted with all necessary terminals and cable glands.

General ordering data

| | |
|------------|---|
| Version | Klippon POK (polyester empty enclosure), Earthing plate, Miscellaneous, Height: 60.5 mm, Width: 438 mm, Depth: 0.8 mm, Material: Brass, polished, untreated |
| Order No. | 1391010000 |
| Type | KLIPPON COPL 163609 |
| GTIN (EAN) | 4050118191332 |
| Qty. | 5 pc(s). |

KLIPPON COPL 163609**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

| | | | |
|----------------------|---------|----------------------|-------------|
| Depth | 0.8 mm | Depth (inches) | 0.031 inch |
| Height | 60.5 mm | Height (inches) | 2.382 inch |
| Width | 438 mm | Width (inches) | 17.244 inch |
| Wall thickness, min. | 0.8 mm | Wall thickness, max. | 0.8 mm |
| Net weight | 33.8 g | | |

General information

| | | | |
|----------------|---------------------|--------------------|--------|
| Material | Brass | Material thickness | 0.8 mm |
| Surface finish | polished, untreated | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002623 | ETIM 7.0 | EC002623 |
| ETIM 8.0 | EC002623 | ETIM 9.0 | EC002623 |
| ECLASS 9.0 | 27-18-28-14 | ECLASS 9.1 | 27-18-92-64 |
| ECLASS 10.0 | 27-18-28-14 | ECLASS 11.0 | 27-18-28-14 |
| ECLASS 12.0 | 27-18-28-14 | ECLASS 13.0 | 27-18-28-14 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | / |
|------------|---|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | CAD data – STEP |
| Catalogues | Catalogues in PDF-format |
| Brochures | |