

**H0,75/16D GR BD GSP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

- Linked wire-end ferrules on reel (5,000 pcs.)
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |  |
|------------|--|
| Version    | Wire-end ferrule, Standard, 12 mm, 10 mm, grey |
| Order No.  | <a href="#">1476080000</a>                     |
| Type       | H0,75/16D GR BD GSP                            |
| GTIN (EAN) | 4050118282986                                  |
| Qty.       | 5,000 pc(s).                                   |
| Packaging  | Reel   |

**H0,75/16D GR BD GSP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |         |
|------------|---------|
| Net weight | 0.128 g |
|------------|---------|

**Technical data**

|                        |                                    |         |          |
|------------------------|------------------------------------|---------|----------|
| Description of article | Reel of wire end ferrules,<br>grey | Version | Standard |
|------------------------|------------------------------------|---------|----------|

**Wire-end ferrules**

|                             |                      |  |         |
|-----------------------------|----------------------|--|---------|
| Collar diameter (D2)        | 2.8 mm               | Colour code                                | DIN     |
| Conductor cross-section     | 0.75 mm <sup>2</sup> | Contact surface diameter (D1)              | 1.2 mm  |
| Contact surface length (L2) | 10 mm                | L1 in mm                                   | 16 mm   |
| Metal sleeve thickness (S1) | 0.15 mm              | Plastic collar thickness (S2)              | 0.25 mm |
| Stripping length            | 12 mm                | Wire connection cross section AWG,<br>max. | AWG 18  |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |
| ECLASS 12.0 | 27-40-02-01 | ECLASS 13.0 | 27-40-02-01 |

**Environmental Product Compliance**

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

**Approvals**

Approvals



|                       |            |
|-----------------------|------------|
| ROHS                  | Conform    |
| UL File Number Search | UL Website |
| Certificate No. (UR)  | E354986    |

**Downloads**

|                    |  |
|--------------------|--|
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>   |

**H0,75/16D GR BD GSP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**