

**WQB WPD X05/3****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****General ordering data**

|            |                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------|
| Version    | Cross-connector (terminal), Plugged, Number of poles: 3, Pitch in mm (P): 35.60, Insulated: Yes, 135 A, grey |
| Order No.  | <a href="#">1561970000</a>                                                                                   |
| Type       | WQB WPD X05/3                                                                                                |
| GTIN (EAN) | 4050118367133                                                                                                |
| Qty.       | 20 pc(s).                                                                                                    |

**WQB WPD X05/3****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 19.6 mm | Depth (inches)  | 0.772 inch |
| Height     | 14 mm   | Height (inches) | 0.551 inch |
| Width      | 88.4 mm | Width (inches)  | 3.48 inch  |
| Net weight | 19.9 g  |                 |            |

**Temperatures**

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

**Material data**

|          |       |        |      |
|----------|-------|--------|------|
| Material | Wemid | Colour | grey |
|----------|-------|--------|------|

**System specifications**

|         |                 |
|---------|-----------------|
| Version | Cross-connector |
|---------|-----------------|

**Additional technical data**

|                          |         |                |         |
|--------------------------|---------|----------------|---------|
| Explosion-tested version | No      | Type of fixing | Plugged |
| Type of mounting         | Plugged |                |         |

**Dimensions**

|                 |         |
|-----------------|---------|
| Pitch in mm (P) | 35.6 mm |
|-----------------|---------|

**General**

|                 |   |
|-----------------|---|
| Number of poles | 3 |
|-----------------|---|

**Rating data**

|               |       |
|---------------|-------|
| Rated current | 135 A |
|---------------|-------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ETIM 9.0    | EC000489    |
| ECLASS 9.0  | 27-14-11-40 | ECLASS 9.1  | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |
| ECLASS 12.0 | 27-14-11-40 | ECLASS 13.0 | 27-25-03-03 |

**Environmental Product Compliance**

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

**Important note**

|                     |                                           |
|---------------------|-------------------------------------------|
| Product information | Max. 135 A only possible with mid feed-in |
|---------------------|-------------------------------------------|

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### WQB WPD X05/3

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| Engineering Data   | <a href="#">Zuken E3.S</a>                      |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>        |
| Brochures          |                                                 |