

**HSS-HF 4.8-9.5 EL Y75M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

**General ordering data**

|                    |   |
|--------------------|---|
| Version            | TwinMark, Conductor and cable markers, 4.8 - 9.5 mm, yellow |
| Order No.          | <a href="#">1562690000</a>                                  |
| Type               | HSS-HF 4.8-9.5 EL Y75M                                      |
| GTIN (EAN)         | 4050118367522   |
| Qty.               | 1 pc(s).  |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a>       |

## HSS-HF 4.8-9.5 EL Y75M

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |           |                 |               |
|------------|-----------|-----------------|---------------|
| Depth      | 0.77 mm   | Depth (inches)  | 0.03 inch     |
| Width      | 15.1 mm   | Width (inches)  | 0.594 inch    |
| Length     | 75,000 mm | Length (inches) | 2,952.75 inch |
| Net weight | 1,377 g   |                 |               |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -55...105 °C |
|-----------------------------|--------------|

## General data

|                                      |  |                    |
|--------------------------------------|--|--------------------|
| Colour                               | yellow   |                    |
| Halogen                              | No   |                    |
| Length                               | 75,000 mm  |                    |
| Material                             | Polyolefine  |                    |
| Number of markers per combination    | 1 Shrink sleeve reel = Conductor and cable markers |                    |
| Number of markers per packaging unit | Form of supply                                     | Shrink sleeve reel |
| Number per roll                      | 1  |                    |
| Operating temperature range          | -55... 105 °C                                      |                    |
| Operating temperature range, max.    | 105 °C   |                    |
| Operating temperature range, min.    | -55 °C   |                    |
| Printed characters                   | without  |                    |
| Type of printing                     | neutral  |                    |
| Width                                | 15.1 mm  |                    |

## Conductor and cable markers

|                                   |                   |                                  |                        |
|-----------------------------------|-------------------|----------------------------------|------------------------|
| Conductor O.D.                    | 4.8 - 9.5 mm      | Conductor O.D., max.             | 9.5 mm                 |
| Conductor O.D., min.              | 4.8 mm            | Conductor cross-section, max.    | 16 mm <sup>2</sup>     |
| Conductor cross-section, min.     | 4 mm <sup>2</sup> | Cross-section for connected wire | 4 - 16 mm <sup>2</sup> |
| Halogen                           | No                | Rate of shrinkage                | 2:1                    |
| Recommended shrinking temperature | 90 °C             |                                  |                        |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ETIM 9.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |

## Environmental Product Compliance

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

## Important note

|                     |   |
|---------------------|---|
| Product information | External roll holder 1302920000 necessary |
|---------------------|---|

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### HSS-HF 4.8-9.5 EL Y75M

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Approval/Certificate/Document of Conformity [NFX 70-100-1 2006 + NF X 70-100-2 2006](#)  
[BS EN ISO 4589-2 1999](#)


[EN 45545-2:2020](#)

Catalogues [Catalogues in PDF-format](#)

**HSS-HF 4.8-9.5 EL Y75M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany


[www.weidmueller.com](http://www.weidmueller.com)

**Accessories****THM MULTIMARK**

These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | THM MMP EXT.RH             |
| Order No.  | <a href="#">1302920000</a> |
| GTIN (EAN) | 4050118102307              |
| Qty.       | 1 pc(s).                   |
| Type       | THM MMP ROLLER 115         |
| Order No.  | <a href="#">1357420000</a> |
| GTIN (EAN) | 4050118160314              |
| Qty.       | 1 pc(s).                   |
| Type       | THM MMP ROLLER 30          |
| Order No.  | <a href="#">1357430000</a> |
| GTIN (EAN) | 4050118160253              |
| Qty.       | 1 pc(s).                   |

**THM MULTIMARK PLUS**

These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | MM PLUS ROLLER 110         |
| Order No.  | <a href="#">2672590000</a> |
| GTIN (EAN) | 4050118708097              |
| Qty.       | 1 pc(s).                   |

**HSS-HF 4.8-9.5 EL Y75M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Ink ribbons**

These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.

**General ordering data**

|            |                             |            |
|------------|-----------------------------|------------|
| Type       | RIBBON HSS HF EL 40/300 ... | Version    |
| Order No.  | <a href="#">1426210000</a>  | Ink ribbon |
| GTIN (EAN) | 4050118228823               |            |
| Qty.       | 1 pc(s).                    |            |