


VT SF 1/21 MC NE GE V0**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration



SlimFix are conductor and cable markers with a space-saving design. The markers can be fitted even after the conductor has been installed. They consist of halogen-free material and comply with flammability rating V0/V2. SlimFix is an acknowledged and accredited marker type for traffic engineering applications. The SF tool allows easy installation, even in case of small markers.

Advantages:

- Halogen-free material
- Flammability rating V0/V2
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor cross-section is larger than 16.0 mm²
- Markers in proven MultiCard format

General ordering data

| | |
|--------------------|--|
| Version | SlimFix, Conductor and cable markers, 1.7 - 2.1 mm, 21 x 3.2 mm, yellow |
| Order No. | 1689390004 |
| Type | VT SF 1/21 MC NE GE V0 |
| GTIN (EAN) | 4008190872328 |
| Qty. | 800 pc(s). |
| compatible printer | 2715590000 2438520000 2438510000 |

VT SF 1/21 MC NE GE V0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Depth | 3.2 mm | Depth (inches) | 0.126 inch |
| Height | 21 mm | Height (inches) | 0.827 inch |
| Width | 3.2 mm | Width (inches) | 0.126 inch |
| Net weight | 0.274 g | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -50...120 °C |
|-----------------------------|--------------|

General data

| | |
|--------------------------------------|---|
| Colour | yellow |
| Halogen | No |
| Material | Polyamide 66 |
| Number of markers per combination | 1 MultiCard = Conductor and cable markers |
| Number of markers per packaging unit | Form of supply MultiCard |
| Operating temperature range | -50...120 °C |
| Operating temperature range, max. | 120 °C |
| Operating temperature range, min. | -50 °C |
| Recommended industries | Transportation, Machinery |
| Size of labelling field | 21 x 3.2 mm |
| Type of printing | neutral |
| UL 94 flammability rating | V-0 |
| Width | 3.2 mm |

Conductor and cable markers

| | | | |
|-------------------------------|---------------------|----------------------------------|----------------------------|
| Conductor O.D. | 1.7 - 2.1 mm | Conductor O.D., max. | 2.1 mm |
| Conductor O.D., min. | 1.7 mm | Conductor cross-section, max. | 0.75 mm ² |
| Conductor cross-section, min. | 0.5 mm ² | Cross-section for connected wire | 0.5 - 0.75 mm ² |
| Halogen | No | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ECLASS 9.0 | 27-40-04-01 | ECLASS 9.1 | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | / |
|------------|---|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | CAD data – STEP |
| Engineering Data | Zuken E3.S |
| Catalogues | Catalogues in PDF-format |

Creation date July 5, 2024 2:12:01 AM CEST

Catalogue status 29.06.2024 / We reserve the right to make technical changes.

VT SF 1/21 MC NE GE V0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

