

**WSM 10 NEUTRAL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration

WSM is a complete marking system for cables, conductors, pipes and components - it offers permanent labelling in environments which no other marker is able to withstand. This product line consists of labelling plates, carriers and stainless steel cable ties – available individually or complete in the WSM Set and Service Box.

**Advantages:**

- Sturdy embossed characters for maximum legibility
- Resistant to heat, cold, corrosion, acids, chemicals, fire, etc.
- Individual and multi-character markings, can also be combined
- Quick installation
- Ideal for outdoor applications
- Easy attachment with cable ties

**General ordering data**

|            |  |
|------------|--|
| Version    | Stainless steel markers, Conductor and cable markers, 5.5 x 9.9 mm, silver |
| Order No.  | <a href="#">1712502000</a>   |
| Type       | WSM 10 NEUTRAL   |
| GTIN (EAN) | 4032248052844  |
| Qty.       | 200 pc(s).   |

**WSM 10 NEUTRAL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Depth      | 0.3 mm | Depth (inches)  | 0.012 inch |
| Height     | 5.5 mm | Height (inches) | 0.217 inch |
| Width      | 9.9 mm | Width (inches)  | 0.39 inch  |
| Net weight | 0.13 g |                 |            |

**Temperatures**

|                             |        |
|-----------------------------|--------|
| Operating temperature range | 250 °C |
|-----------------------------|--------|

**General data**

|                                      |  |                |
|--------------------------------------|--|----------------|
| Colour                               | silver   |                |
| Material                             | Stainless steel 1.4404                         |                |
| Number of markers per combination    | 1 Component part = Conductor and cable markers |                |
| Number of markers per packaging unit | Form of supply                                 | Component part |
| Operating temperature range          | 250 °C   |                |
| Operating temperature range, max.    | 250 °C   |                |
| Type of printing                     | neutral  |                |
| Width                                | 9.9 mm   |                |

**Conductor and cable markers**

|                                  |                          |                               |                    |
|----------------------------------|--------------------------|-------------------------------|--------------------|
| Conductor cross-section, max.    | 500 mm <sup>2</sup>      | Conductor cross-section, min. | 16 mm <sup>2</sup> |
| Cross-section for connected wire | 16 - 500 mm <sup>2</sup> |                               |                    |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ETIM 9.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |

**Environmental Product Compliance**

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|            |  |
|------------|--|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|--|