

**HDC 16A SLU 1M25G****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

**General ordering data**

|            |   |
|------------|---|
| Version    | HDC enclosures, Size: 5, Protection degree: IP65, IP65 (in plugged condition), Base housing, End-locking clamp, lower side, Standard, Size of cable entries: M 25 |
| Order No.  | <a href="#">1902330000</a>  |
| Type       | HDC 16A SLU 1M25G   |
| GTIN (EAN) | 4032248591916   |
| Qty.       | 1 pc(s).  |

## HDC 16A SLU 1M25G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                             |         |                            |            |
|-----------------------------|---------|----------------------------|------------|
| Depth                       | 96 mm   | Depth (inches)             | 3.78 inch  |
| Height                      | 57 mm   | Height (inches)            | 2.244 inch |
| Width                       | 62.7 mm | Width (inches)             | 2.468 inch |
| Mounting dimension - height | 40 mm   | Mounting dimension - width | 64 mm      |
| Net weight                  | 222 g   |                            |            |

## Dimensions

|                      |           |                      |       |
|----------------------|-----------|----------------------|-------|
| Cable entry          | w. thread | Height of base B1    | 4 mm  |
| Height of housing B  | 57 mm     | Hole pitch length A2 | 64 mm |
| Total length housing | 79 mm     | Width base C1        | 50 mm |
| Width housing C      | 29.5 mm   |                      |       |

## General data

|                             |                             |                       |                                   |
|-----------------------------|-----------------------------|-----------------------|-----------------------------------|
| EMC housings                | No                          | Housing main material | diecast aluminium                 |
| Material of locking element | Stainless steel, rust-proof | Protection degree     | IP65, IP65 (in plugged condition) |
| Surface finish              | Powder coating              | Tightening torque     | 0.5 Nm                            |

## Version

|                              |                               |                                |              |
|------------------------------|-------------------------------|--------------------------------|--------------|
| BG                           | 5                             | Cable entry                    | w. thread    |
| Clamp version                | End-locking clamp             | Colour (RAL)                   | RAL 7035     |
| Design                       | Standard                      | Design of housing              | Base housing |
| Design of locking system     | End-locking clamp, lower side | Internal thread                | M 25         |
| Number of cable entry on top | 0                             | Number of cable entry sideways | 1            |
| Size                         | 5                             | Size of cable entries          | M 25         |
| Tightening torque            | 0.5 Nm                        | Top part/bottom part/lid       | lower part   |
| Type                         | Base housing                  |                                |              |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000437    | ETIM 7.0    | EC000437    |
| ETIM 8.0    | EC000437    | ETIM 9.0    | EC000437    |
| ECLASS 9.0  | 27-44-02-02 | ECLASS 9.1  | 27-44-02-02 |
| ECLASS 10.0 | 27-44-02-02 | ECLASS 11.0 | 27-44-02-02 |
| ECLASS 12.0 | 27-44-02-02 | ECLASS 13.0 | 27-44-02-02 |

|                     |                         |
|---------------------|-------------------------|
| Substance           | Acetone                 |
| Chemical resistance | Conditionally resistant |
| Substance           | Drilling oil            |
| Chemical resistance | Resistant               |
| Substance           | Diesel                  |
| Chemical resistance | Resistant               |
| Substance           | Ethyl alcohol           |
| Chemical resistance | Resistant               |
| Substance           | Transmission oil        |
| Chemical resistance | Resistant               |

## HDC 16A SLU 1M25G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|                     |                         |
|---------------------|-------------------------|
| Substance           | Hydraulic oil           |
| Chemical resistance | Resistant               |
| Substance           | Coolant                 |
| Chemical resistance | Resistant               |
| Substance           | Petroleum benzine       |
| Chemical resistance | Resistant               |
| Substance           | Sweat                   |
| Chemical resistance | Resistant               |
| Substance           | Premium gasoline        |
| Chemical resistance | Conditionally resistant |
| Substance           | Water                   |
| Chemical resistance | Resistant               |
| Substance           | UV                      |
| Chemical resistance | Unstable                |
| Substance           | Ozone                   |
| Chemical resistance | Unstable                |

## Environmental Product Compliance

|                     |  |
|---------------------|--|
| REACH SVHC          | Lead 7439-92-1 Potassium perfluorobutane sulfonate 29420-49-3  |
| SCIP                | e98b2b24-ba23-41bf-8d19-Odda3647412f   |
| Chemical resistance | de.myview.objectmodel.impl.BlockImpl@1ebb5ea7 de.myview.objectmodel.impl.BlockImpl@230aa9e2<br>de.myview.objectmodel.impl.BlockImpl@4be83db2 de.myview.objectmodel.impl.BlockImpl@41bd6dd1<br>de.myview.objectmodel.impl.BlockImpl@5375d27 de.myview.objectmodel.impl.BlockImpl@7384a1da<br>de.myview.objectmodel.impl.BlockImpl@790b17b5 de.myview.objectmodel.impl.BlockImpl@53f22ea0<br>de.myview.objectmodel.impl.BlockImpl@6c939f9c de.myview.objectmodel.impl.BlockImpl@3acf79a5<br>de.myview.objectmodel.impl.BlockImpl@1b5877f6 de.myview.objectmodel.impl.BlockImpl@591ddd13<br>de.myview.objectmodel.impl.BlockImpl@2902d6d3 |

## Approvals

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate No. (cURus) | E92202     |

## Downloads

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        | <a href="#">FL FIELDWIRING EN</a>        |

**HDC 16A SLU 1M25G****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Cover**

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

**General ordering data**

|            |                            |   |
|------------|----------------------------|---|
| Type       | HDC 16A DMDL 2BO           | Version   |
| Order No.  | <a href="#">1665910000</a> | HDC enclosures, Size: 5, Protection degree: IP65 (in plugged condition), Cover for upper part of housing, End-locking clamp, lower side, Standard |
| GTIN (EAN) | 4008190422943              |   |
| Qty.       | 1 pc(s).                   |   |