

SQV 6/4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

General ordering data

| | |
|------------|--|
| Version | Cross-connector (terminal), when screwed in, Number of poles: 4, Pitch in mm (P): 18.00, Insulated: No, 125 A, black, grey |
| Order No. | 2615100000 |
| Type | SQV 6/4 |
| GTIN (EAN) | 4050118653885 |
| Qty. | 50 pc(s). |

SQV 6/4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

| | | | |
|------------|---------|-----------------|------------|
| Depth | 32 mm | Depth (inches) | 1.26 inch |
| Height | 7.5 mm | Height (inches) | 0.295 inch |
| Width | 61.1 mm | Width (inches) | 2.406 inch |
| Net weight | 17.42 g | | |

Temperatures

| | |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

Material data

| | | | |
|----------|----|--------|-------------|
| Material | PA | Colour | black, grey |
|----------|----|--------|-------------|

System specifications

| | |
|---------|-----------------|
| Version | Cross-connector |
|---------|-----------------|

Additional technical data

| | | | |
|--------------------------|-----------------|----------------|-----------------|
| Explosion-tested version | No | Type of fixing | when screwed in |
| Type of mounting | when screwed in | | |

Cross-connector

| | | | |
|---------------------------|-------|------|-----------------|
| Rated current, multi-pole | 125 A | Type | Cross-connector |
|---------------------------|-------|------|-----------------|

Dimensions

| | |
|-----------------|-------|
| Pitch in mm (P) | 18 mm |
|-----------------|-------|

General

| | |
|-----------------|---|
| Number of poles | 4 |
|-----------------|---|

Rating data

| | |
|---------------|-------|
| Rated current | 125 A |
|---------------|-------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000489 | ETIM 7.0 | EC000489 |
| ETIM 8.0 | EC000489 | ETIM 9.0 | EC000489 |
| ECLASS 9.0 | 27-14-11-40 | ECLASS 9.1 | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |
| ECLASS 12.0 | 27-14-11-40 | ECLASS 13.0 | 27-25-03-03 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | / |
|------------|---|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

SQV 6/4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Engineering Data

[CAD data – STEP](#)

Catalogues

[Catalogues in PDF-format](#)