

**CABTITE BP 7MM PA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The blanking plugs are used for the safe closing of un-needed cable passages in the sealing elements.

**General ordering data**

Version	Blind plug, Cabtite (cable entry system), Polyamide, white, Height: 16 mm, Width: 7 mm, Depth: 16 mm, -40 °C...120 °C, IP66
Order No.	<a href="#">2652350000</a>
Type	CABTITE BP 7MM PA
GTIN (EAN)	4050118662450
Qty.	25 pc(s).

**CABTITE BP 7MM PA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

Depth	16 mm	Depth (inches)	0.63 inch
Height	16 mm	Height (inches)	0.63 inch
Width	7 mm	Width (inches)	0.276 inch
Length	16 mm	Length (inches)	0.63 inch
Diameter	7 mm	Net weight	0.52 g

**Temperatures**

Operating temperature	-40 °C... 120 °C
-----------------------	------------------

**General information**

Halogen	No	Material	Polyamide
Outer cable diameter, max.	7 mm	Outer cable diameter, min.	7 mm
Protection degree	IP66	UL 94 flammability rating	V-0

**Classifications**

ETIM 6.0	EC000879	ETIM 7.0	EC000879
ETIM 8.0	EC000879	ETIM 9.0	EC000879
ECLASS 9.0	27-14-44-21	ECLASS 9.1	27-14-44-21
ECLASS 10.0	27-14-44-21	ECLASS 11.0	27-14-44-21
ECLASS 12.0	27-14-08-07	ECLASS 13.0	27-14-08-07

**Environmental Product Compliance**

REACH SVHC	/
------------	---

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">CAD data – STEP</a>
User Documentation	<a href="#">Cabtite Installation Instructions</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>