

IE-EBR-MODULE-RS232-ALM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Module for saving and loading a device configuration**

- Reduce system downtime by simple reconfiguration in case of replacing devices
- 2 storage spaces selectable via DIP switch
- Compact, rugged, reliable design
- For use with switches of Advanced- and SubstationLine

General ordering data

Version	Configuration backup and restore module, IP40, -10 °C...60 °C
Order No.	2682610000
Type	IE-EBR-MODULE-RS232-ALM
GTIN (EAN)	4050118692105
Qty.	1 pc(s).

IE-EBR-MODULE-RS232-ALM

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	90.25 mm	Depth (inches)	3.553 inch
Height	14.5 mm	Height (inches)	0.571 inch
Width	32 mm	Width (inches)	1.26 inch
Net weight	118 g		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-10 °C...60 °C
Humidity	5 to 95 % (non-condensing)		

EMC conformity and approvals

EMC standards	EN 55032, EN 55024, FCC Part 15 Subpart B Class A, IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV, IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m	Free fall	According to IEC 60068-2-31
Safety standard	UL 61010-1, UL 61010-2-201	Shock	according to IEC 60068-2-27
Vibration	according to IEC 60068-2-6		

Environmental conditions

Humidity	5 to 95 % (non-condensing)	Operating altitude	≤ 2000 m
Operating temperature, max.	60 °C	Operating temperature, min.	-10 °C
Storage temperature, max.	85 °C	Storage temperature, min.	-40 °C

Guarantee

Time interval	3 years
---------------	---------

Interfaces

Function DIP switch	1x for selection of the configuration storage space (A or B), 1x for selection between upload or download of a configuration	Function start button	Starts the upload or download of a configuration
LED indicator	power, data transmitting, transmission status		

MTBF

MTBF	According to Standard	Telcordia SR-332
------	-----------------------	------------------

Power supply

Connection type	RJ45
Current consumption	Voltage 5 V
	Current 0.14 A
Voltage supply	5 V DC (via RS-232 RTS signal of serial console port)

IE-EBR-MODULE-RS232-ALM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Technical data**

Cable length	210 mm	Housing main material	PC molding
Protection degree	IP40		

Classifications

ETIM 6.0	EC001068	ETIM 7.0	EC001068
ETIM 8.0	EC001068	ETIM 9.0	EC001068
ECLASS 9.1	19-15-07-90	ECLASS 10.0	19-15-07-90
ECLASS 11.0	19-17-03-04	ECLASS 12.0	19-17-03-04
ECLASS 13.0	19-17-03-04	ECLASS 14.0	19-17-03-04

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
SCIP	9229992a-00b9-4096-8962-200a7f33e289
RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	7a, 7cl

Approvals

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate no. (cULus)	E141197

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity RCM Declaration of Conformity UK Declaration of Conformity
User Documentation	Hardware Installation Guide
Catalogues	Catalogues in PDF-format