

IE-C5DD4UG0030DSAXXX-E**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**General ordering data**

| | |
|------------|---|
| Version | Dragline cable, PROFINET, M8 D-code - IP67 angled socket, Open, Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B), PUR, 3 m |
| Order No. | 2706160030 |
| Type | IE-C5DD4UG0030DSAXXX-E |
| GTIN (EAN) | 4050118743005 |
| Qty. | 1 pc(s). |

IE-C5DD4UG0030DSAXXX-E

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|-------------|
| Length | 3 m | Length (inches) | 118.11 inch |
| Net weight | 189.9 g | | |

Temperatures

| | | | |
|--------------------------|----------------|-----------------------|----------------|
| Storage temperature | -50 °C...70 °C | Operating temperature | -40 °C...70 °C |
| Installation temperature | -20 °C...60 °C | | |

Cable specific standards

| | | | |
|-------------------------------|---|------------------------------|--------------------------|
| Standard, insulating material | DIN EN 50290-2-23 (VDE 0819) Table 2/A (HD 624.3) | Standard, shielding material | DIN EN 13602 Cu-ETP-A..B |
| Standard, wire material | DIN EN 13602 Cu-ETP-A | | |

General standards

| | |
|--------------------|-----------------|
| Connector standard | IEC 61076-2-114 |
|--------------------|-----------------|

Standards

| | | | |
|------------------------------|--------------------------|-------------------------------|---|
| Connector standard | IEC 61076-2-114 | Standard, insulating material | DIN EN 50290-2-23 (VDE 0819) Table 2/A (HD 624.3) |
| Standard, shielding material | DIN EN 13602 Cu-ETP-A..B | Standard, wire material | DIN EN 13602 Cu-ETP-A |

Cable structure

| | | | |
|------------------------------|---|---------------------------------------|---|
| Arrangement of wire cores | Star-quad | Colour sequence or wires - wire pairs | white, yellow, blue, orange |
| Complete shielding | Aluminium foil, Shielding braid made from copper wiring | Cross-section | 4*AWG 22/7 - 0.32 mm ² |
| Diameter of inner sheathing | 3.9 mm | Filler | As central element |
| Insulation | PE | Insulation cross-section | 1.5 mm |
| Material sheath | PUR | Number of wires | 4 |
| Overlap of shielding braid | 85 % | Sheath diameter, max. | 6.7 mm |
| Sheath diameter, min. | 6.3 mm | Sheathing colour | green (RAL 6018) |
| Sheathing material thickness | 0.9 mm | Shielding | SF/UTP |
| Shielding braid thickness | 0.13 mm | Standard designations | 2YH(ST)C11Y 2x2x0.75/1.5-100 LI VZN GN FRNC |
| Strands | 7 | Wire core insulation thickness | 0.38 mm |
| Wire material | Stranded tin-plated copper wire | | |

Electrical properties of cable

| | | | |
|--------------------------------|--------------------------------------|-------------------------------|---|
| Capacity at 1 kHz | 52 nF/km | Category | Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B) |
| Characteristic impedance | 100 ± 15 Ω at 1-100 MHz | Delay skew | 40 ns/100m |
| Loop resistance | 120 Ω/km | Operating voltage (UL rating) | 600 V |
| Operating voltage, UL | 600 V | Resistance differential | 3 % |
| Signal propagation time | 5.3 ns/m | Speed | 180 m/min |
| Test voltage: wire-wire-shield | 2000 V _{eff} , 50 Hz, 1 min | Transfer impedance | 20 mΩ/m at 10 MHz |

Creation date July 7, 2024 10:35:29 PM CEST

IE-C5DD4UG0030DSAXXX-E

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Mechanical and material properties of cable

| | | | |
|---------------------------------|--|--------------------------------|--------------------------------|
| Abrasion resistance | very good | Acceleration | 4 m/s ² |
| Bending cycles | 3 Mio | Fire propagation | No |
| Halogen | halogen-free, according to IEC 60754-2 | Min. bending radius, once only | 5 x cable diameter |
| Min. bending radius, repetitive | 7.5 x cable diameter | Pulling force | ≤ 150 N |
| Resistance to oils | in accordance with IEC 60811-2-1 | Resistance to spread of flame | in accordance with IEC 60332-1 |
| Silicone-free | Yes | Speed | 180 m/min |
| UV-resistant | Yes | | |

Plug, left

| | |
|-----------|--|
| Plug left | M8, D-coded, IP67, female contact, angled 90°, plug, Plastic, shielded |
|-----------|--|

Plug, right

| | |
|------------|--------------------|
| Plug right | free conductor end |
|------------|--------------------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002599 | ETIM 7.0 | EC002599 |
| ETIM 8.0 | EC002599 | ETIM 9.0 | EC002599 |
| ECLASS 9.0 | 27-06-03-08 | ECLASS 9.1 | 27-06-03-08 |
| ECLASS 10.0 | 27-06-03-08 | ECLASS 11.0 | 27-06-03-08 |
| ECLASS 12.0 | 27-06-03-08 | ECLASS 13.0 | 27-06-03-08 |

Environmental Product Compliance

| | |
|------------|--------------------------------------|
| REACH SVHC | Lead 7439-92-1 |
| SCIP | 67cf1078-beca-4687-860b-dc475a6ec24a |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads


| | |
|------------------|--|
| Engineering Data | CAD data – STEP |
| Catalogues | Catalogues in PDF-format |

IE-C5DD4UG0030DSAXXX-E**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Drawings****Dimensioned drawing**

M8

| | |
|---|--------|
| 1 | yellow |
| 2 | white |
| 3 | orange |
| 4 | blue |