

**IE-C5DD4UG0300DCSU20-E****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**General ordering data**

|            |   |
|------------|---|
| Version    | Dragline cable, PROFINET, M8 D-code - IP67 straight pin, RJ45 IP 20, Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B), PUR, 30 m |
| Order No.  | <a href="#">2706250300</a>  |
| Type       | IE-C5DD4UG0300DCSU20-E  |
| GTIN (EAN) | 4050118743197   |
| Qty.       | 1 pc(s).  |

## IE-C5DD4UG0300DCSU20-E

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |                |
|------------|---------|-----------------|----------------|
| Length     | 30 m    | Length (inches) | 1,181.102 inch |
| Net weight | 1,851 g |                 |                |

## Temperatures

|                          |                |                       |                |
|--------------------------|----------------|-----------------------|----------------|
| Storage temperature      | -50 °C...70 °C | Operating temperature | -40 °C...70 °C |
| Installation temperature | -20 °C...60 °C |                       |                |

## Cable specific standards

|                               |   |                              |                          |
|-------------------------------|---|------------------------------|--------------------------|
| Standard, insulating material | DIN EN 50290-2-23 (VDE 0819) Table 2/A (HD 624.3) | Standard, shielding material | DIN EN 13602 Cu-ETP-A..B |
| Standard, wire material       | DIN EN 13602 Cu-ETP-A                             |                              |                          |

## General standards

|                    |                                 |
|--------------------|---------------------------------|
| Connector standard | IEC 61076-2-114, IEC 60603-7-51 |
|--------------------|---------------------------------|

## Standards

|                              |                                 |                               |   |
|------------------------------|---------------------------------|-------------------------------|---|
| Connector standard           | IEC 61076-2-114, IEC 60603-7-51 | Standard, insulating material | DIN EN 50290-2-23 (VDE 0819) Table 2/A (HD 624.3) |
| Standard, shielding material | DIN EN 13602 Cu-ETP-A..B        | Standard, wire material       | DIN EN 13602 Cu-ETP-A                             |

## Cable structure

|                              |   |                                       |   |
|------------------------------|---|---------------------------------------|---|
| Arrangement of wire cores    | Star-quad   | Colour sequence or wires - wire pairs | white, yellow, blue, orange                       |
| Complete shielding           | Aluminium foil, Shielding braid made from copper wiring | Cross-section                         | 4*AWG 22/7 - 0.32 mm <sup>2</sup>                 |
| Diameter of inner sheathing  | 3.9 mm  | Filler                                | As central element                                |
| Insulation                   | PE  | Insulation cross-section              | 1.5 mm  |
| Material sheath              | PUR   | Number of wires                       | 4   |
| Overlap of shielding braid   | 85 %  | Sheath diameter, max.                 | 6.7 mm  |
| Sheath diameter, min.        | 6.3 mm  | Sheathing colour                      | green (RAL 6018)                                  |
| Sheathing material thickness | 0.9 mm  | Shielding                             | SF/UTP  |
| Shielding braid thickness    | 0.13 mm   | Standard designations                 | 2YH(ST)C11Y<br>2x2x0.75/1,5-100 LI VZN<br>GN FRNC |
| Strands                      | 7   | Wire core insulation thickness        | 0.38 mm   |
| Wire material                | Stranded tin-plated copper wire                         |                                       |   |

## IE-C5DD4UG0300DCSU20-E

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Electrical properties of cable

|                                |                                      |                               |   |
|--------------------------------|--------------------------------------|-------------------------------|---|
| Capacity at 1 kHz              | 52 nF/km                             | Category                      | Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B) |
| Characteristic impedance       | 100 ± 15 Ω at 1–100 MHz              | Delay skew                    | 40 ns/100m                                  |
| Loop resistance                | 120 Ω/km                             | Operating voltage (UL rating) | 600 V                                       |
| Operating voltage, UL          | 600 V                                | Resistance differential       | 3 %   |
| Signal propagation time        | 5.3 ns/m                             | Speed                         | 180 m/min                                   |
| Test voltage: wire-wire-shield | 2000 V <sub>eff</sub> , 50 Hz, 1 min | Transfer impedance            | 20 mΩ/m at 10 MHz                           |

## Mechanical and material properties of cable

|                                 |  |                                |                                |
|---------------------------------|--|--------------------------------|--------------------------------|
| Abrasion resistance             | very good                              | Acceleration                   | 4 m/s <sup>2</sup>             |
| Bending cycles                  | 3 Mio                                  | Fire propagation               | No                             |
| Halogen                         | halogen-free, according to IEC 60754-2 | Min. bending radius, once only | 5 x cable diameter             |
| Min. bending radius, repetitive | 7.5 x cable diameter                   | Pulling force                  | ≤ 150 N                        |
| Resistance to oils              | in accordance with IEC 60811-2-1       | Resistance to spread of flame  | in accordance with IEC 60332-1 |
| Silicone-free                   | Yes                                    | Speed                          | 180 m/min                      |
| UV-resistant                    | Yes                                    |                                |                                |

## Plug, left

|           |  |
|-----------|--|
| Plug left | M8, D-coded, IP67, male contact, straight, plug, Plastic, shielded |
|-----------|--|

## Plug, right

|            |   |
|------------|---|
| Plug right | RJ45, IP20, male contact, straight, plug, Plastic, shielded |
|------------|---|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002599    | ETIM 7.0    | EC002599    |
| ETIM 8.0    | EC002599    | ETIM 9.0    | EC002599    |
| ECLASS 9.0  | 27-06-03-08 | ECLASS 9.1  | 27-06-03-08 |
| ECLASS 10.0 | 27-06-03-08 | ECLASS 11.0 | 27-06-03-08 |
| ECLASS 12.0 | 27-06-03-08 | ECLASS 13.0 | 27-06-03-08 |
| ECLASS 14.0 | 27-06-03-08 |             |             |

## Environmental Product Compliance

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| REACH SVHC                           | Lead 7439-92-1                       |
| SCIP                                 | 67cf1078-beca-4687-860b-dc475a6ec24a |
| RoHS Compliance Status               | Compliant with exemption             |
| RoHS Exemption (if applicable/known) | 6c                                   |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|            |  |
|------------|--|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|--|

Creation date October 4, 2024 5:53:14 AM CEST

Catalogue status 28.09.2024 / We reserve the right to make technical changes.

**IE-C5DD4UG0300DCSU20-E****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Dimensioned drawing**

| RJ45 |        | M8 |
|------|--------|----|
| 1    | yellow | 1  |
| 3    | white  | 2  |
| 2    | orange | 3  |
| 6    | blue   | 4  |