


**SFX-VT 9/24 MM BL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Highly flexible: SFX**

SFX markers are the preferred choice for labelling cables if you prefer the classic cable tie solution. Cables do not always run in a straight line. The material used in SFX markers addresses this fact with highly flexible polyurethane. The marker follows each curve of the cable and latches on with ease. Your advantages at a glance: Weathering resistance tested according to ISO DIN EN ISO 4892-2:2013 table 3, procedure A cycle 1 at 5000 hours

Individually labeled with the M-Print® PRO  
Easy and fast printing with the THM MultiMark

**General ordering data**

|            |   |
|------------|---|
| Version    | SlimFix, Conductor and cable markers, 7 -, 26 x 15 mm, blue |
| Order No.  | <a href="#">2799320000</a>                                  |
| Type       | SFX-VT 9/24 MM BL   |
| GTIN (EAN) | 4064675261155   |
| Qty.       | 1,000 pc(s).  |

**SFX-VT 9/24 MM BL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Height     | 26 mm   | Height (inches) | 1.024 inch |
| Width      | 15 mm   | Width (inches)  | 0.591 inch |
| Net weight | 0.279 g |                 |            |

**Temperatures**

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -55...105 °C |
|-----------------------------|--------------|

**General data**

|                                   |              |                                   |              |
|-----------------------------------|--------------|-----------------------------------|--------------|
| Colour                            | blue         | Halogen                           | No           |
| Material                          | Polyolefine  | Operating temperature range       | -55...105 °C |
| Operating temperature range, max. | 105 °C       | Operating temperature range, min. | -55 °C       |
| Printed characters                | without      | Size of labelling field           | 23.5 x 9 mm  |
| Type of printing                  | neutral      | UL 94 flammability rating         | HB           |
| Version                           | halogen-free | Width                             | 15 mm        |

**Conductor and cable markers**

|                      |         |                |     |
|----------------------|---------|----------------|-----|
| Cable tie passage    | Flat    | Conductor O.D. | 7 - |
| Conductor O.D., min. | 7 mm    | Halogen        | No  |
| Suitable cable tie   | Plastic |                |     |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ETIM 9.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |

**Environmental Product Compliance**

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |   |
|------------------|---|
| Engineering Data | <a href="#">CAD data – STEP</a>   |
| White paper      | <a href="#">Fact Sheet PV Markierer</a><br><a href="#">Fact Sheet EN PV Markers</a> |
| Catalogues       | <a href="#">Catalogues in PDF-format</a>  |

### SFX-VT 9/24 MM BL

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



**SFX-VT 9/24 MM BL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Ink ribbons**

These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.

**General ordering data**

|            |                            |            |
|------------|----------------------------|------------|
| Type       | RIBBON MM-HS 60/300 SW     | Version    |
| Order No.  | <a href="#">2448880000</a> | Ink ribbon |
| GTIN (EAN) | 4050118462944              |            |
| Qty.       | 1 pc(s).                   |            |