

SFX-M 11/60 LRP AL RT SDR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**General ordering data**

| | |
|------------|--|
| Version | MetalliCard, Conductor and cable markers, 7 - 40 mm, 60 x 11 mm, red |
| Order No. | 2859550000 |
| Type | SFX-M 11/60 LRP AL RT SDR |
| GTIN (EAN) | 4064675572305 |
| Qty. | 1 pc(s). |

SFX-M 11/60 LRP AL RT SDR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|---------|-----------------|------------|
| Depth | 0.8 mm | Depth (inches) | 0.031 inch |
| Height | 60 mm | Height (inches) | 2.362 inch |
| Width | 11 mm | Width (inches) | 0.433 inch |
| Net weight | 0.853 g | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -55...130 °C |
|-----------------------------|--------------|

General data

| | | |
|--------------------------------------|---|-------------|
| Colour | red | |
| Material | Anodized aluminium | |
| Number of markers per combination | 1 MetalliCard = Conductor and cable markers | |
| Number of markers per packaging unit | Form of supply | MetalliCard |
| Operating temperature range | -55... 130 °C | |
| Operating temperature range, max. | 130 °C | |
| Operating temperature range, min. | -55 °C | |
| Recommended industries | Process, Energy | |
| Size of labelling field | 11.2 x 45 mm | |
| Type of printing | To customer specification | |
| Width | 11 mm | |

Conductor and cable markers

| | | | |
|----------------------------------|--------------------------|-------------------------------|--------------------|
| Cable tie passage | Raised | Conductor O.D. | 7 - 40 mm |
| Conductor O.D., max. | 40 mm | Conductor O.D., min. | 7 mm |
| Conductor cross-section, max. | 500 mm ² | Conductor cross-section, min. | 16 mm ² |
| Cross-section for connected wire | 16 - 500 mm ² | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ECLASS 9.0 | 27-40-04-01 | ECLASS 9.1 | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | / |
|------------|---|

Downloads

| | |
|------------------|--|
| Engineering Data | CAD data – STEP |
| Catalogues | Catalogues in PDF-format |

SFX-M 11/60 LRP AL RT SDR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

