

FUSE WSFL 22X58 75A 1K5V GPV**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**General ordering data**

Version	Photovoltaics, Cartridge fuse, 1500 V, 22x58, gPV, 75 A
Order No.	2870900000
Type	FUSE WSFL 22X58 75A 1K5V GPV
GTIN (EAN)	4064675636458
Qty.	10 pc(s).

FUSE WSFL 22X58 75A 1K5V GPV**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Height	58 mm	Height (inches)	2.283 inch
Width	22 mm	Width (inches)	0.866 inch
Net weight	50 g		

Fuse cartridge

Fuse-link standard	IEC 60269-6, gPV (EN 60269-6)	Current	75 A
Rated DC voltage	1,500 V	Power dissipation, max.	12.6 W

Classifications

ETIM 7.0	EC002704	ETIM 8.0	EC002704
ETIM 9.0	EC002704	ECLASS 11.0	27-14-20-02
ECLASS 12.0	27-14-20-02	ECLASS 13.0	27-14-20-02
ECLASS 14.0	27-14-20-02		

Environmental Product Compliance

REACH SVHC	/
RoHS Compliance Status	Compliant without exemption

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	FUSE WSFL 22X58 40A 1K5V GPV
Catalogues	Catalogues in PDF-format

FUSE WSFL 22X58 75A 1K5V GPV

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

