

IE-S1ES2LE-100**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Single pair Ethernet is a technology that only requires one pair of wires to transmit data and power. The resulting benefits will make SPE the preferred network at the field level and beyond.

Advantages of Single Pair Ethernet

- Consistent: Single Pair Ethernet enables uniform Ethernet-based communication from the sensor to the cloud
- Future-proof: key technology for Industry 4.0 and IIoT
- Flexible: ranges of up to 1000 m and transmission properties of up to 1 Gbps enable use across applications
- Innovative: lighter, less space required, and reduced installation effort

General ordering data

Order No.	2926140000
Type	IE-S1ES2LE-100
GTIN (EAN)	4099986643277
Qty.	1 pc(s).

IE-S1ES2LE-100

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	100 m	Length (inches)	3,937.008 inch
Net weight	1,823 g		

Technical specifications for cable

Colour coding	white / blue	Configurable cable length	No
Halogen	halogen-free, according to IEC 60754-2, halogen-free, according to IEC 60754-1	Insulation	PE
Number of poles	2	Number of wires	2
Resistance to spread of flame	in accordance with IEC 60332-1-2	Sheath material	LSZH
Sheathing colour	black	Shielded	Yes
Suitable for cable carriers	No		

Cable specific standards

Impervious to smoke	According to IEC 61034
---------------------	------------------------

Standards

Impervious to smoke	According to IEC 61034
---------------------	------------------------

Cable structure

Arrangement of wire cores	Twisted pair	Colour coding	white / blue
Complete shielding	Shielding braid made from copper wiring	Cross-section	1 x 2 x AWG 26/7 - 0.132 mm ²
Insulation	PE	Insulation cross-section	1.15 mm
Material sheath	LSZH	Number of wires	2
Sheath diameter, max.	3.7 mm	Sheathing colour	black
Shielding	S/FTP	Strands	7
Tensile force, max.	14 N	Wire pair shielding	Aluminium foil

Electrical properties of cable

Category	T1-B	Coupling attenuation 1 to 600 MHz	Type I
Coupling attenuation up to 1000 MHz	70 dB	Separating class according to EN 50174-2	d

Mechanical and material properties of cable

Colour	black	Halogen	halogen-free, according to IEC 60754-2, halogen-free, according to IEC 60754-1
Impervious to smoke	According to IEC 61034	Min. bending radius, once only	28 mm
Min. bending radius, repetitive	56 mm	Resistance to spread of flame	in accordance with IEC 60332-1-2

Classifications

ETIM 6.0	EC000830	ETIM 7.0	EC003249
ETIM 8.0	EC003249	ETIM 9.0	EC003249
ECLASS 9.0	27-06-18-05	ECLASS 9.1	27-06-90-90
ECLASS 10.0	27-06-18-01	ECLASS 11.0	27-06-18-01
ECLASS 12.0	27-06-18-01	ECLASS 13.0	27-06-18-01

Creation date July 2, 2024 10:16:09 PM CEST

IE-S1ES2LE-100

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform
------	---------

Downloads

Catalogues	Catalogues in PDF-format
------------	--

IE-S1ES2LE-100

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

