

**U-OS-PWEB-ES-RT-10000/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

PROCON-WEB Embedded System is easy to install on u-OS through the app manager.

To implement the optimal web-based HMI solution, PROCON-WEB Embedded System offers the following features:

- Roles and rights based user management
- Extensive alarming
- predefined controls, such as buttons, sliders, text fields or image areas
- powerful more complex controls, like iframes, charts, tables
- flexible scripting for maximum flexibility
- Historian functionality for storage and visualization of historical data
- connection to the controller via communication driver

**General ordering data**

Version	Visualization software, Platform for runtime system: u-OS compatible devices, Number of process variables, max.: 10000, Number of HMI-devices, max.: 5
Order No.	<a href="#">2942050000</a>
Type	U-OS-PWEB-ES-RT-10000/5
Qty.	1 pc(s).

**U-OS-PWEB-ES-RT-10000/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

Net weight	0
------------	---

**Features of the runtime**

Platform for runtime system	u-OS compatible devices	Number of HMI-devices, max.	5
Maximum number of drivers	1	Projectable by	PROCON-WEB Designer
Runtime features	Simple and complex controls, Alarming, Historian, User-Management, Process connection via communication drivers		

**Licence information**

Licence coverage	One-time licence	Licence type	Software licence
Licensing by	WIBU Ticket ID	Number of process variables, max.	10,000

**System data**

Number of HMI-devices, max.	5	Number of process variables, max.	10,000
Operating system	u-OS	Platform for runtime system	u-OS compatible devices

**System requirements**

Minimal disk space needed	0.1 GB	Minimal memory (RAM) needed	0.1 GB
Operating system	u-OS		

**Classifications**

ETIM 6.0	EC001416	ETIM 7.0	EC001416
ETIM 8.0	EC001416	ETIM 9.0	EC001416
ECLASS 9.0	27-24-25-02	ECLASS 9.1	27-24-25-02
ECLASS 10.0	27-24-25-02	ECLASS 11.0	27-24-25-02
ECLASS 12.0	27-24-25-02	ECLASS 13.0	27-24-25-02
ECLASS 14.0	27-24-25-02		

**Environmental Product Compliance**

RoHS Compliance Status	Not affected
REACH SVHC	No SVHC above 0.1 wt%

**Downloads**

Catalogues	<a href="#">Catalogues in PDF-format</a>
------------	--