

**WTZ4 PT100/2 C 0/4-20mA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Do not use product for new developments, Only remaining stock available



RTD temperature signal converters for connecting resistance temperature sensors and analogue DC current or voltage outputs.

A variety of resistance thermometers (e.g., PT100) are used to measure temperature in an industrial environment. These are used with 2-, 3-, or 4-wire technology.

We distinguish here between PTC and NTC thermistors. For an exact temperature measurement, the resistance value must be logged, linearised and converted into an analogue signal proportional to the temperature.

Signal isolating converters carry out these important functions. They isolate signals between the harsh industrial environments and the downstream electronics. Furthermore, they compensate for potential differences caused by long cable lengths.

Sensor-related inadequacies such as cold joints and linearity errors are also minimised.

**General ordering data**

Version	RTD transformer, PT100, 2-conductor connection, Configurable, Input : Temperature, PT100 (2-wire), Output : 0(4)-20 mA
Order No.	<a href="#">8432220000</a>
Type	WTZ4 PT100/2 C 0/4-20mA
GTIN (EAN)	4032248110391
Qty.	1 pc(s).
Delivery status	<b>This article will no longer be available in the future.</b>
Available until	2023-12-30
Alternative product	<a href="#">7760054183</a>

## WTZ4 PT100/2 C 0/4-20mA

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Depth	112.4 mm	Depth (inches)	4.425 inch
Width	12.5 mm	Width (inches)	0.492 inch
Length	92.4 mm	Length (inches)	3.638 inch
Net weight	77.4 g		

## Temperatures

Storage temperature	-20 °C...85 °C	Operating temperature	0 °C...55 °C
---------------------	----------------	-----------------------	--------------

## Probability of failure

SIL in compliance with IEC 61508	None
----------------------------------	------

## Input

Number of inputs	1	Sensor	PT100 (2 wire)
Sensor supply	1.45 mA	Temperature input range	Adjustable from -200...+800°C

## Output

Load impedance current	≤ 500 Ω	Number of outputs	1
Output current	0...20 mA, 4...20 mA		

## General data

Accuracy	± 0.5 % of measuring range	Configuration	DIP switch, Potentiometer, and PT100-Simulator
Current consumption	< 48 mA @ I <sub>OUT</sub> = 20 mA	Galvanic isolation	Without isolation
Linearity	Yes	Protection degree	IP20
Rail		Temperature coefficient	Measuring range ≥ 200 K: &le; 200 ppm/K (typ. 80 ppm/K) 100 K ≤ measuring range < 200 K: < 250 ppm/K (typ. 100 ppm/K)
Voltage supply	TS 35 24 V DC ± 20 %		

## Insulation coordination

EMC standards	EN 55011, EN 61000-6	Galvanic isolation	Without isolation
---------------	----------------------	--------------------	-------------------

## Connection data

Type of connection	Tension-clamp connection	Stripping length, rated connection	7 mm
Clamping range, rated connection	1.5 mm <sup>2</sup>	Clamping range, min.	0.5 mm <sup>2</sup>
Clamping range, max.	2.5 mm <sup>2</sup>		

## Classifications

ETIM 6.0	EC002919	ETIM 7.0	EC002919
ETIM 8.0	EC002919	ETIM 9.0	EC002919
ECLASS 9.0	27-21-01-29	ECLASS 9.1	27-21-01-29
ECLASS 10.0	27-21-01-29	ECLASS 11.0	27-21-01-29
ECLASS 12.0	27-21-01-29	ECLASS 13.0	27-21-01-29

## WTZ4 PT100/2 C 0/4-20mA

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

## Tender specification sheets

## Long specification

**PT100 temperature measuring transformer, configured with DIP switches, 2-wire connection technology**

RTD measurement isolating transformer in 12.5 mm width with external power supply, for transmitting PT100- 2-wire signals.

Input temperature range **-200...+800 °C.**

Analogue DC signals (0(4) to 20 mA) are available on the output side.

Zero/span compensation with potentiometer.

Add-on housing for TS35 rail mounting

Dimensions: L/W/H 92.4/12.5/ 112.4 mm

Tension-clamp connection / Nominal cross-section 1.5 mm<sup>2</sup>

Protection degree: IP 20

Input PT100, 2-wire Output 0/4...20 mA Load resistance Transmission error typ. 200 ppm / °C

Auxiliary power 24 VDC

+/- 20 % Ambient temperature range 0°C...+55 °C

Isolation no electrical isolation Approvals cULus, CSA

Type **WTZ4 PT100/2 C 0/4-20mA**

## Short specification

**PT100 temperature measuring transformer, configured with DIP switches, 2-wire connection technology**

RTD measurement isolating transformer in 12.5 mm width with external power supply, for transmitting

PT100 2-wire signals. Input temperature range

**-200...+800 °C.**

Analogue DC signals (0(4) to 20 mA) are available on the output side.

Zero/span compensation with potentiometer.

## Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

SCIP

c2a21576-d875-4548-ae68-5e7f85ddf0c7

## Important note

Product information

This product will soon be replaced by a new product.

Please do not use with new systems. Please contact our technical support.

## Approvals

Approvals



ROHS

Conform

UL File Number Search

UL Website

Certificate no. (cULus)

E141197

Creation date July 1, 2024 2:17:30 AM CEST

Catalogue status 14.06.2024 / We reserve the right to make technical changes.

### WTZ4 PT100/2 C 0/4-20MA

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Approval/Certificate/Document of Conformity

[Application notes – Declaration of Conformity](#)

Engineering Data

[CAD data – STEP](#)

Product Change Notification

[20220218 Technical change - WAVE series' signal conditioners WS WZ](#)

User Documentation

[Device description – Instruction sheet](#)

Catalogues

[Catalogues in PDF-format](#)


Brochures

**WTZ4 PT100/2 C 0/4-20mA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Electric symbol****Similar to illustration**

## WTZ4 PT100/2 C 0/4-20MA

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

## General ordering data

Type	WS 10/5 MC NE WS	Version
Order No.	<a href="#">1635000000</a>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4008190261948	Allen-Bradley, white
Qty.	720 pc(s).	

2.5 mm<sup>2</sup>


2.5  
mm<sup>2</sup>

The plug-in cross-connections feature easy handling and quick installation. This saves a great deal of time during installation in comparison with screwed solutions.

## General ordering data

Type	ZQV 2.5N/2 SW	Version
Order No.	<a href="#">1718080000</a>	W-Series, Cross-connector, 24 A
GTIN (EAN)	4008190349301	
Qty.	60 pc(s).	
Type	ZQV 2.5N/2 GE	Version
Order No.	<a href="#">1693800000</a>	W-Series, Cross-connector, 24 A
GTIN (EAN)	4008190883621	
Qty.	60 pc(s).	
Type	ZQV 2.5N/2 RT	Version
Order No.	<a href="#">1717900000</a>	W-Series, Cross-connector, 24 A
GTIN (EAN)	4008190349288	
Qty.	60 pc(s).	

**WTZ4 PT100/2 C 0/4-20MA****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories**

Type	ZQV 2.5N/2 BL	Version
Order No.	<a href="#">1717990000</a>	W-Series, Cross-connector, 24 A
GTIN (EAN)	4008190349295	
Qty.	60 pc(s).	