

**H0,25/10T GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- supplied loose in polybag
- Weidmüller colour code

**General ordering data**

|            |  |
|------------|--|
| Version    | Wire-end ferrule, Standard, 8 mm, 6 mm, yellow |
| Order No.  | <a href="#">9021010000</a>                     |
| Type       | H0,25/10T GE                                   |
| GTIN (EAN) | 4008190109103                                  |
| Qty.       | 500 pc(s).                                     |
| Packaging  | loose  |

**H0,25/10T GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |        |
|------------|--------|
| Net weight | 0.04 g |
|------------|--------|

**Technical data**

|                        |  |         |          |
|------------------------|--|---------|----------|
| Description of article | Wire end ferrule with plastic collar, yellow | Version | Standard |
|------------------------|--|---------|----------|

**Wire-end ferrules**

|                             |                      |   |               |
|-----------------------------|----------------------|---|---------------|
| Collar diameter (D2)        | 1.8 mm               | Colour code                             | Telemecanique |
| Conductor cross-section     | 0.25 mm <sup>2</sup> | Contact surface diameter (D1)           | 0.8 mm        |
| Contact surface length (L2) | 6 mm                 | L1 in mm                                | 10 mm         |
| Metal sleeve thickness (S1) | 0.15 mm              | Plastic collar thickness (S2)           | 0.25 mm       |
| Stripping length            | 8 mm                 | Wire connection cross section AWG, max. | AWG 24        |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |
| ECLASS 12.0 | 27-40-02-01 | ECLASS 13.0 | 27-40-02-01 |

**Environmental Product Compliance**

|            |   |
|------------|---|
| REACH SVHC | / |
|------------|---|

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |  |
|--------------------|--|
| Engineering Data   | <a href="#">CAD data – STEP</a>  |
| Engineering Data   | <a href="#">Zuken E3.S</a>   |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>   |
| Brochures          |  |

**H0,25/10T GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**