

POK MOPL 1222**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

The Klippon® POK enclosure range is made from a high-quality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class are a requirement.

Key features of the extensive product range:

- Available in 17 sizes
- Two standard finishes (colours): grey (similar to RAL 7001 for industrial use) and black (similar to RAL 9011 for harsh environments, Ex)
- Cover with stainless steel screws in cross-head / slotted design
- Moulded gasket made of silicone or chloroprene
- Fixing holes outside the sealed area to ensure high ingress protection of IP66
- Impact resistance up to 7 Joules
- Mounting directly in the enclosure or using an internal mounting plate
- Direct wall mounting possible using fixing holes or mounting feet
- Fastening thread to attach mounting rails and plates
- Up to E60 fire rating dependent on the configuration
- Weidmüller can manufacture and supply this enclosure to match customer specifications - fitted with all necessary terminals and cable glands.

General ordering data

| | |
|------------|---|
| Version | Klippon POK (polyester empty enclosure), Mounting plate, Height: 107 mm, Width: 207 mm, Depth: 1.5 mm, Material: Sheet steel, galvanized, Miscellaneous, silver |
| Order No. | 9510600000 |
| Type | POK MOPL 1222 |
| GTIN (EAN) | 4008190498238 |
| Qty. | 1 pc(s). |

POK MOPL 1222**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

| | | | |
|-----------------------------|--------|----------------------------|------------|
| Depth | 1.5 mm | Depth (inches) | 0.059 inch |
| Height | 107 mm | Height (inches) | 4.213 inch |
| Width | 207 mm | Width (inches) | 8.15 inch |
| Mounting dimension - height | 52 mm | Mounting dimension - width | 193 mm |
| Net weight | 237 g | | |

General information

| | | | |
|----------------|-------------------------|--------------------|-----------------|
| Material | Sheet steel, galvanized | Material thickness | 1.5 mm |
| Surface finish | Miscellaneous | Type of fixing | when screwed in |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000213 | ETIM 7.0 | EC000213 |
| ETIM 8.0 | EC000213 | ETIM 9.0 | EC000213 |
| ECLASS 9.0 | 27-40-06-39 | ECLASS 9.1 | 27-18-92-90 |
| ECLASS 10.0 | 27-40-06-39 | ECLASS 11.0 | 27-40-06-39 |
| ECLASS 12.0 | 27-40-06-39 | ECLASS 13.0 | 27-40-06-39 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | / |
|------------|---|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | CAD data – STEP |
| Catalogues | Catalogues in PDF-format |
| Brochures | |

POK MOPL 1222**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Accessories****Depth 7.5 mm**

The system accessories for the Klippon® K enclosure series allows you to easily adapt the enclosures to meet the specific requirements of every application.

- DIN Rails TS 35 and TS 15
- Mounting plates
- Hinges
- Wall-mounted holder

General ordering data

| | | |
|------------|----------------------------|--|
| Type | TS35X7.5 ST K5 1 | Version |
| Order No. | 8000003907 | Rail, TS 35, TS 35 x 7.5, Width: 203 mm, without slot, Steel, galvanic |
| GTIN (EAN) | 4050118652642 | zinc plated and passivated |
| Qty. | 20 pc(s). | |